The rawfonts package

Alan Jeffrey

v0.01

This file is maintained by the LaTeX Project team.
Bug reports can be opened (category `tools`) at
http://latex-project.org/bugs.html.

Overview

The `rawfonts` LaTeX 2$_\varepsilon$ package is used to provide emulation of LaTeX 2.09 documents which used low-level commands such as `\tenrm`. If you say:

```
\usepackage{rawfonts}
```

then over sixty fonts such as `\tenrm` will be loaded into LaTeX. This has a large overhead, for example this document uses:

```
8221 words of font info for 30 fonts
```

but when run with the `rawfonts` package it uses:

```
19294 words of font info for 73 fonts
```

That is `rawfonts` can cause your document to load twice as many fonts. (This overhead is why LaTeX 2$_\varepsilon$ does not define `\tenrm` and friends by default.)

If you want to only load a small number of fonts, you can use the `only` option, for example to only load `\tenrm` and `\tensf`:

```
\usepackage[only,tenrm,tensf]{rawfonts}
```

The `rawfonts` package is intended mainly for use with LaTeX 2.09 documents, and you might want to have the package loaded every time you use LaTeX 2$_\varepsilon$ in compatibility mode. In this case, you should add the line:

```
\RequirePackage{rawfonts}
```

to your `latex209.cfg` LaTeX 2.09 compatibility configuration file.

Implementation

The driver for the documentation you're now reading.

```
⟨*driver⟩
\documentclass{ltxdoc}
\begin{document}
\DocInput{rawfonts.dtx}
\end{document}
⟨/driver⟩
```

This is a LaTeX 2_ε package.

```
⟨*package⟩
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{rawfonts}
   [1994/05/08 Low-level LaTeX 2.09 font compatibility]
```

The `rawfonts` package uses the `somedefs` package.

```
\RequirePackage{somedefs}
```

By default, all the fonts are loaded, but the `only` option says that only the ones specified as options should be.

```
\UseAllDefinitions
\DeclareOption{only}{\UseSomeDefinitions}
\DeclareOption*{\UseDefinition{\CurrentOption}}
\ProcessOptions
```

The rest of the code loads fonts. Five point:

```
\ProvidesDefinition{\DeclareFixedFont{\fivrm}{OT1}{cmr}{m}{n}{\@vpt}}
\ProvidesDefinition{\DeclareFixedFont{\fivmi}{OML}{cmm}{m}{it}{\@vpt}}
\ProvidesDefinition{\DeclareFixedFont{\fivsy}{OMS}{cmsy}{m}{n}{\@vpt}}
\ProvidesDefinition{\DeclareFixedFont{\fivly}{U}{lasy}{m}{n}{\@vpt}}
```

Six point:

```
\ProvidesDefinition{\DeclareFixedFont{\sixrm}{OT1}{cmr}{m}{n}{\@vipt}}
\ProvidesDefinition{\DeclareFixedFont{\sixmi}{OML}{cmm}{m}{it}{\@vipt}}
\ProvidesDefinition{\DeclareFixedFont{\sixsy}{OMS}{cmsy}{m}{n}{\@vipt}}
\ProvidesDefinition{\DeclareFixedFont{\sixly}{U}{lasy}{m}{n}{\@vipt}}
```

Seven point:

```
\ProvidesDefinition{\DeclareFixedFont{\sevrm}{OT1}{cmr}{m}{n}{\@viipt}}
\ProvidesDefinition{\DeclareFixedFont{\sevmi}{OML}{cmm}{m}{it}{\@viipt}}
\ProvidesDefinition{\DeclareFixedFont{\sevsy}{OMS}{cmsy}{m}{n}{\@viipt}}
\ProvidesDefinition{\DeclareFixedFont{\sevit}{OT1}{cmr}{m}{it}{\@viipt}}
\ProvidesDefinition{\DeclareFixedFont{\sevly}{U}{lasy}{m}{n}{\@viipt}}
```

Eight point:

```
\ProvidesDefinition{\DeclareFixedFont{\egtrm}{OT1}{cmr}{m}{n}{\@viiipt}}
\ProvidesDefinition{%
                    \DeclareFixedFont{\egtmi}{OML}{cmm}{m}{it}{\@viiipt}}
\ProvidesDefinition{%
                    \DeclareFixedFont{\egtsy}{OMS}{cmsy}{m}{n}{\@viiipt}}
\ProvidesDefinition{%
     \DeclareFixedFont{\egtit}{OT1}{cmr}{m}{it}{\@viiipt}}
\ProvidesDefinition{\DeclareFixedFont{\egtly}{U}{lasy}{m}{n}{\@viiipt}}
```

Nine point:

```
\ProvidesDefinition{\DeclareFixedFont{\ninrm}{OT1}{cmr}{m}{n}{\@ixpt}}
```

```
\ProvidesDefinition{\DeclareFixedFont{\ninmi}{OML}{cmm}{m}{it}{\@ixpt}}
\ProvidesDefinition{\DeclareFixedFont{\ninsy}{OMS}{cmsy}{m}{n}{\@ixpt}}
\ProvidesDefinition{\DeclareFixedFont{\ninit}{OT1}{cmr}{m}{it}{\@ixpt}}
\ProvidesDefinition{\DeclareFixedFont{\ninbf}{OT1}{cmr}{bx}{n}{\@ixpt}}
\ProvidesDefinition{\DeclareFixedFont{\nintt}{OT1}{cmtt}{m}{n}{\@ixpt}}
\ProvidesDefinition{\DeclareFixedFont{\ninly}{U}{lasy}{m}{n}{\@ixpt}}
```

Ten point:

```
\ProvidesDefinition{\DeclareFixedFont{\tenrm}{OT1}{cmr}{m}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tenmi}{OML}{cmm}{m}{it}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tensy}{OMS}{cmsy}{m}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tenit}{OT1}{cmr}{m}{it}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tensl}{OT1}{cmr}{m}{sl}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tenbf}{OT1}{cmr}{bx}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tentt}{OT1}{cmtt}{m}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tensf}{OT1}{cmss}{m}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tenly}{U}{lasy}{m}{n}{\@xpt}}
\ProvidesDefinition{\DeclareFixedFont{\tenex}{OMX}{cmex}{m}{n}{\@xpt}}
```

Eleven point:

```
\ProvidesDefinition{\DeclareFixedFont{\elvrm}{OT1}{cmr}{m}{n}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvmi}{OML}{cmm}{m}{it}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvsy}{OMS}{cmsy}{m}{n}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvit}{OT1}{cmr}{m}{it}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvsl}{OT1}{cmr}{m}{sl}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvbf}{OT1}{cmr}{bx}{n}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvtt}{OT1}{cmtt}{m}{n}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvsf}{OT1}{cmss}{m}{n}{\@xipt}}
\ProvidesDefinition{\DeclareFixedFont{\elvly}{U}{lasy}{m}{n}{\@xipt}}
```

Twelve point:

```
\ProvidesDefinition{\DeclareFixedFont{\twlrm}{OT1}{cmr}{m}{n}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlmi}{OML}{cmm}{m}{it}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlsy}{OMS}{cmsy}{m}{n}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlit}{OT1}{cmr}{m}{it}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlsl}{OT1}{cmr}{m}{sl}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlbf}{OT1}{cmr}{bx}{n}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twltt}{OT1}{cmtt}{m}{n}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlsf}{OT1}{cmss}{m}{n}{\@xiipt}}
\ProvidesDefinition{\DeclareFixedFont{\twlly}{U}{lasy}{m}{n}{\@xiipt}}
```

Fourteen point:

```
\ProvidesDefinition{\DeclareFixedFont{\frtnrm}{OT1}{cmr}{m}{n}{\@xivpt}}
\ProvidesDefinition{%
                    \DeclareFixedFont{\frtnmi}{OML}{cmm}{m}{it}{\@xivpt}}
\ProvidesDefinition{%
                    \DeclareFixedFont{\frtnsy}{OMS}{cmsy}{m}{n}{\@xivpt}}
\ProvidesDefinition{%
                    \DeclareFixedFont{\frtnbf}{OT1}{cmr}{bx}{n}{\@xivpt}}
\ProvidesDefinition{\DeclareFixedFont{\frtnly}{U}{lasy}{m}{n}{\@xivpt}}
```

Seventeen point:

```
\ProvidesDefinition{%
                    \DeclareFixedFont{\svtnrm}{OT1}{cmr}{m}{n}{\@xviipt}}
\ProvidesDefinition{%
                   \DeclareFixedFont{\svtnmi}{OML}{cmm}{m}{it}{\@xviipt}}
```

```
\ProvidesDefinition{%
                   \DeclareFixedFont{\svtnsy}{OMS}{cmsy}{m}{n}{\@xviipt}}
\ProvidesDefinition{%
                   \DeclareFixedFont{\svtnbf}{OT1}{cmr}{bx}{n}{\@xviipt}}
\ProvidesDefinition{\DeclareFixedFont{\svtnly}{U}{lasy}{m}{n}{\@xviipt}}
```

Twenty point:

```
\ProvidesDefinition{\DeclareFixedFont{\twtyrm}{OT1}{cmr}{m}{n}{\@xxpt}}
\ProvidesDefinition{\DeclareFixedFont{\twtymi}{OML}{cmm}{m}{it}{\@xxpt}}
\ProvidesDefinition{\DeclareFixedFont{\twtysy}{OMS}{cmsy}{m}{n}{\@xxpt}}
\ProvidesDefinition{\DeclareFixedFont{\twtyly}{U}{lasy}{m}{n}{\@xxpt}}
```

Twenty-five point:

```
\ProvidesDefinition{\DeclareFixedFont{\twfvrm}{OT1}{cmr}{m}{n}{\@xxvpt}}
```

That's it.

⟨/package⟩